5

10

15

25

WHAT IS CLAIMED IS:

- 1. A formed article of thermoplastic resin, comprising a fiber-reinforced resin material of a thermoplastic resin containing reinforcing fibers and incorporating therein additionally as a sliding property-imparting agent a material having a storage elastic modulus in the range of $3.5 \times 10^8 \, \mathrm{Pa}$ to $5.0 \times 10^8 \, \mathrm{Pa}$ in a service temperature range of $30^\circ\mathrm{C}$ to $70^\circ\mathrm{C}$.
- 2. The formed article according to claim 1, wherein said thermoplastic resin is selected from the group consisting of polybutylene terephthalate, polyethylene terephthalate, polycarbonate, and polyamide.
- 3. The formed article according to claim 1, wherein said thermoplastic resin is polybutylene terephthalate.
- 4. The formed article according to claim 1, wherein said sliding property-imparting agent is selected from the group consisting of fluoropolymers and polyethylene.
- 5. The formed article according to claim 1, wherein said sliding property-imparting agent is polytetrafluoroethylene.
- 6. The formed article according to claim 1, wherein said reinforcing fiber is present in an amount of 20 to 60% by weight, based on the weight of said thermoplastic resin.
 - 7. The formed article according to claim 1, wherein said reinforcing fiber is at least one member selected from the group consisting of glass fibers, carbon fibers, and metal fibers.
 - 8. The formed article according to claim 1, wherein said formed article is a slider for use in a slide fastener.
 - 9. A formed article of thermoplastic resin, comprising a

10

15

20

25

fiber-reinforced resin material of a polyamide-based resin containing reinforcing fibers and incorporating therein additionally as a sliding property-imparting agent a material having a storage elastic modulus in the range of 3.5×10^8 Pa to 5.0×10^8 Pa in a service temperature range of 30°C to 70°C at a ratio in the range of 4 to 10° by weight, based on the total weight of said resin and said reinforcing fibers.

- 10. The formed article according to claim 9, wherein said sliding property-imparting agent is selected from the group consisting of fluoropolymers and polyethylene.
- 11. The formed article according to claim 9, wherein said sliding property-imparting agent is polytetrafluoroethylene.
- 12. The formed article according to claim 9, wherein said reinforcing fiber is present in an amount of 20 to 60% by weight, based on the weight of said polyamide-based resin.
- 13. The formed article according to claim 9, wherein said reinforcing fiber is at least one member selected from the group consisting of glass fibers, carbon fibers, and metal fibers.
- 14. The formed article according to claim 9, wherein said formed article is a slider for use in a slide fastener.
 - 15. A formed article of thermoplastic resin, comprising a fiber-reinforced resin material of a thermoplastic resin (excluding a polyamide-based resin) containing reinforcing fibers and incorporating therein additionally as a sliding property-imparting agent a material having a storage elastic modulus in the range of 3.5×10^8 Pa to 5.0×10^8 Pa in a service temperature range of 30° C to 70° C at a ratio in the range of 4 to 20° 8 by weight, based

10

15

on the total weight of said resin and said reinforcing fibers.

- 16. The formed article according to claim 15, wherein said thermoplastic resin is selected from the group consisting of polybutylene terephthalate, polyethylene terephthalate, and polycarbonate.
- 17. The formed article according to claim 15, wherein said thermoplastic resin is polybutylene terephthalate.
- 18. The formed article according to claim 15, wherein said sliding property-imparting agent is selected from the group consisting of fluoropolymers and polyethylene.
- 19. The formed article according to claim 15, wherein said sliding property-imparting agent is polytetrafluoroethylene.
- 20. The formed article according to claim 15, wherein said reinforcing fiber is present in an amount of 20 to 60% by weight, based on the weight of said thermoplastic resin.
- 21. The formed article according to claim 15, wherein said reinforcing fiber is at least one member selected from the group consisting of glass fibers, carbon fibers, and metal fibers.
- 22. The formed article according to claim 15, wherein said
 20 formed article is a slider for use in a slide fastener.